Urovo

DT66

Enterprise Mobile Computer

- 6.5-inch ultra-high-definition (720*1600) thin-bezel display, offers more information at one page and less scrolling.
- Supports front screen and back NFC reading to meet diverse usage needs.
- The 5000mAh smart battery with a built-in battery management system enhancing overall battery life. With the hot swap feature, it achieves uninterrupted 24-hour operation.
- Powered by the latest Qualcomm 2.4GHz high-performance processor, it delivers exceptional processing speed, further empowering faster decoding of 1D/2D/DPM barcode.
- Wi-Fi 6E and 5G delivers the super fast and reliable wireless connections.
- Optional iToF camera for three-dimensional volume measurement of parcel.

















Smart Battery











Cradle

2.4GHz Processor

Android 13 O.S.

Sealing

Display

DT66 Enterprise Mobile Computer



Processor

Octa-core 2.4GHz

• O.S.

Android 13, upgradable to Android 18 Support GMS/AER

Memory

RAM: 4GB ROM: 64GB RAM: 8GB ROM: 128GB (optional) Micro-SD card, Up to 256 GB

Display

6.5 inch display, 720*1600

· Touch Screen

Ultra sensitive capacitive touch panel, support multi-touch, works with gloves and wet fingers

Dimensions

Dimensions: 175.8 mm L x 76.5 mm W x 14.5 mm D Weight: About 283g

Specifications

Scanning

Professional scan engine Support international standard 1D/2D barcode; Support barcode displayed on

· Camera

Front: 5MP FF; Rear: 13MP PDAF Optional iToF camera

Sensors

Light + Accelerator+ Proximity + Geomagnetic + Gyro+Pressure(optional)

Audio

Dual-Microphone with noise cancellation, 1.5W Speaker for loud noise, reciever supports echo cancellation

Battery

Capacity: 3.85V 5000mAh Support hot swap

Buttons

PWR button Vol+/- button Scan button*2 Custom button

Slots

Nano- SIM x 2, Micro-SD Slot x 1, (Reserved support eSIM)

·Communication

5G/4G/3G/2G Bluetooth: BT5.2 + BR/EDR + BLE Wi-Fi: Wi-Fi 6E, 2.4G/5G Support 2x2 MU-MIMO, IEEE 802.11a/b/g/n/ac/d/e/h/i/k/r/v/w/ax

Roaming: 802.11a/0/g/ll/ac/dre/ll/l/ Air);OKC/;PMKID caching

Positioning

GPS BEIDOU GLONASS Galileo

Protection

IP67 1.5m drop resistance

Environmental

Operating Temp.: $-20 \sim +60$ °C Storage Temp.: $-40 \sim +70$ °C

Humidity: 5%RH ~ 95%RH(No condensation)

ESD: +/-15kv Air: +/-8kv contact