PM452



1

0

💌 🖬 🚨 💿

NEXT GENERATION HANDHELD TERMINAL FOR THE STATE-OF-THE-ART SCANNING PERFORMANCE

Fine-Tuned for Maximum Data Capture Efficiency

Introducing the PM452, a powerhouse in handheld terminal te chnology, meticulously engineered to deliver unparalleled scanning performance in any environment. With powerful scan engine options, including an extra-long-range and a flexible range scanner with dynamic reading capabilities, the PM452 provides fast and accurate reading of various symbologies. With a robust 2.2 GHz processor and ample 6 GB RAM / 128 GB flash memory, the device excels in processing data and decoding symbologies quickly, even in challenging conditions such as low lighting or damaged barcodes. The 13 MP camera on top of the device, equipped with PDAF (Phase Detection Auto Focus) technology, captures clear images in a split second.

Enhanced Connectivity for Seamless Operations

The PM452 sets new standards in connectivity and efficiency with Wi-Fi 6E, enhancing data security, preserving battery life, and ensuring swift data transmission. Its advanced network capacity empowers businesses to effortlessly manage larger datasets, catalyzing productivity growth. With the LTE option, workers can utilize the device seamlessly throughout the entire supply chain, leading to uninterrupted operations. The optional 5,700 mAh extended battery gives users enough power to stay connected and productive all day, wherever they are.

Choose Your Ideal Device

Choose from a standard range 1D/2D imager or opt for the extra-long-range one that boasts an incredible reading distance of up to 29 m when reading certain types of symbologies. Tailor your PM452 further with three keypad options: numeric, function numeric, or alphanumeric. To enhance efficiency further, consider the optional ergonomically designed, detachable Gun Handle which boosts productivity in your workforce.

Pragmatic Device for Any Size of Business

PM452 is well-equipped with the latest technologies, including Android 13, advanced scan engines, and Wi-Fi 6E, while remaining as a pragmatic choice for businesses of all sizes. Its exceptional durability keeps maintenance simple and downtime low. With IP65 water/dust resistance, a 2.0 m (6.6 ft.) drop resistance to concrete at room temperature, and an operating temperature ranging from -20 °C to 60 °C (-4 °F to 140 °F), the PM452 is well protected and suitable for any type of work setting.

Industries

Transport & Logistics Manufacturing Warehouse Management

Accessories

Standard AC/DC Power Adaptor Country Plug LCD Protection Film USB-C Cable Battery - Standard: 4,000 mAh - Extended: 5,700 mAh Stylus Wristband

Optional

Single Slot Cradle (opt. Ethernet) 4 Slot Cradle 4 Slot Battery Charger Gun Trigger

1

ø

د 🗢 🗉 👗

6 e • 4 0

👗 💤 🗉 M 🧕



PM452

Main processor			
Octa-core @ 2.2 GHz			
Operating system			
Google Android (GMS & AOSP)	Android 13 (upgradable to Android 18)* FOTA (Firmware Over The Air) update		
Memory and stora	ge		
RAM / Flash micro SD SIM	4 GB / 64 GB or 6 GB / 128 GB Supports up to 512 GB using ExFAT file systen 1 micro SIM		
Sensor	Proximity sensor, Light ambient sensor, Accelerometer, Gyro sensor		
PHYSICAL C	HARACTERISTICS		
Dimensions	214.9 x 77.3 x 39.3 mm 8.5 x 3.0 x 1.6 in.		
Weight	450 g / 15.9 oz.		
Display	4.3", IPS panel (480 x 800 pixel), WVGA LED backlight Daylight readable (max. 500+ nits) Wideviewing angle Multi-touch capacitive Corning Gorilla glass		
Power			
Standard battery Extended battery Back-up battery	4,000 mAh, 3.7 V, Li-ion rechargeable 5,700 mAh, 3.63 V, Li-ion rechargeable 60 mAh, 3.7 V (10C), Hot-Swap		
Keypad			
Three options	Numeric, Function Numeric, Alpha numeric		
Voice & Audio	Built-in microphone Dual speakers		
Standard communications	USB 2.0 Type-C/OTG POGO 7 pin		
Notification	LED on top: power (R/G), warning (R/B) LED on side: scan status (R/B)		

GLOBAL NAVIGATION SATELLITE SYSTEM

WLAN SKU: No GNSS WWAN SKU: GNSS receiver support for GPS (A-GPS), GLONASS, Galileo, and Beidou

WIRELESS Wireless WAN		
Wireless LAN		
Radio	IEEE 802.11 a/b/g/n/ac/ax/d/h/i/k/r/v, Wi-Fi 6E, Wi-Fi Direct and Hot Spot support, 1x1 MU-MIMO	
Data rates	6 GHz: 802.11 ax: Up to 867 Mbps 5 GHz: 802.11 a/n/ac/ax: Up to 867 Mbps 2.4 GHz: 802.11 b/g/n/ax: Up to 143 Mbps	
Operating channels	1 to 13 (2412~2472 MHz) 36 to 165 (5180~5825 MHz) 1 to 233 (5955~7115 MHz)	
Channel bandwidth	20, 40, 80, 160 MHz	
Security and encryption	WEP / WPA / WPA2 / WEP, RC4 Algorithm / TKIP, RC4 Algorithm / AES, Rijndael Algorithm, EAP-FAST / EAP-TLS / EAP-TTLS / PEAP-GTC / PEAP-MSCHAPv2 / WPA3 Personal / WPA3 Enterpriase / Enhanced Open (OWE)	
Fast Roam	802.11r	
Wireless PAN		
Bluetooth	Class I, ver. 5.2, BLE support	
	JRE	
Integrated scan en	gines	
Three 1D/2D scan extra-long range	engine options including flexible range and	
Camora		

Camera

Тор	13 MP, F. No. 2.0, PDAF (Phase Detection
	Auto Focus), LED flash

NFC (Near Field Communication)

NFC-Forum (NFC-IP Modes)	Reader for NFC Forum (Tag Types 1 to 5)
Reader (PCD - VCD)	ISO/IEC 14443 A, ISO/IEC 14443 B, ISO/IEC 15693, Mifare Classic 1K/4K, Mifare DESFire, Mifare UltraLight©, Sony FeliCa

USER ENVIRONMENT

Operating	-20 °C to 60 °C
temperature	-4 °F to 140 °F
Storage	-40 °C to 70 °C
temperature	-40 °F to 158 °F
Humidity	95% non-condensing

Drop	2.0 m (6.6 ft.) multiple drops to concrete surface at room temperature
	1.8 m (6 ft.) across the operating temperature range, MIL-STD-810H
Tumble	1,000 cycles (2,000 hits), 1.0 m (3.3 ft.) per IEC 60068-2-31 specification
Rain/dust proof (sealing)	IP65
Electrostatic discharge	± 15 kV air discharge ± 8 kV contact discharge

REGULATORY APPROVALS AND COMPLIANCE

CB, CE, RoHS, WEEE, FCC, IC, RCM, KC, NRCan, BIS, WPC, IMDA, NBTC, CITC, SIG

ENTERPRISE SOLUTION



Simple yet powerful management solution

PMDM is a mobile device management solution for managing and monitoring your Point Mobile Android devices.

Centralized management of enterprise devices is vital for better productivity. You should provide a device configuration that the workers can concentrate on their work with the device, and also decrease the device downtime by predicting when to replace the battery, etc.

EmKit Enterprise Mobility Kit

The EmKit[™] is Point Mobile's value-added service kit engineered for the pure benefit of system integrators. EmKit supports the utilization, solution development, and secure management of your business devices.

PULS – ANDROID UPDATE & SECURITY

PULS is a Point Mobile's lifetime solution, which extends the life cycle of Android-based Point Mobile enterprise devices to up to seven years after a product launch.



Stay up-to-date with the latest security updates for up to 7 year Conveniently update your devices in the field by FOTA Update Android Versions** and use new features via PULS

For further information, please visit www.pointmobile.com or contact your regional sales representative.

WARRANTY

Subject to the Terms and Conditions, PM452 carries 1 (one) year-warranty period from the date of purchase against the defective materials and manufacturing defects.

For the further inquiry, please leave your message here: https://www.pointmobile.com/en/contactus.

The Android version may vary based on the mobile processor product roadmap. The upgradeable version is subject to change on the manufacturer's policy and condition.

** Android version updates may come with restrictions and could incur charges.

China Headquarters Point Mobile China info@pointmobile-cn.com +86 755 8869 1169

Corporate Headquarters Point Mobile Co., Ltd. https://www.pointmobile.com/en/contactus +82 2 3397 7870

NA Headquarters Point Mobile Americas LLC info@pointmobileamericas.com +1 202 798 0786

Europe Headquarters

Point Mobile Europe GmbH info.pmeg@pointmobile.com +49 211 1588 5913

Google, Android, Google Play and other marks are trademarks of Google LLC. Copyright © 2006-2024 Point Mobile Co., Ltd. All rights reserved. Point Mobile Co., Ltd. is the designer and manufacturer of handheld mobile computers. The Point Mobile logo is a registered trademark and symbol of Point Mobile. Features and specifications are subject to change without prior notice.

