Mobile

PERFORMANCE CHARACTERISTICS

Main processor Octa-core @2.2 GHz

Operating system

Android 15 Google Android

(GMS)

FOTA (Firmware Over The Air) update

Memory and storage

RAM / FLASH 4 GB / 64 GB (UES) or 8 GB / 128 GB (UES) Supports up to 1 TB using ExFAT file system

micro SD SIM

Sensor

Proximity, light ambient, accelerometer.

gyro, digital compass

1 x nano SIM. 1 x eSIM

PHYSICAL CHARACTERISTICS

272.9 x 175.2 x 11.7 mm * 10.7 x 6.9 x 0.5 in. * Dimensions

10.95" (1920 x 1200 pixels), IPS Display

Daylight readable (typical 500 nits at max.) LED backlight

Wideviewing angle

Power

8,000 mAh, removable, hard-pack Main battery 100 mAh, 3.7 V, 10C (Hot Swap) Back-up battery

PD 3.0 Adapte

AC Input: 100~240 V, 50~60 Hz DC Output: 20W

Kevs & Buttons Volume ±. power

two scan buttons (scanner SKU)

Voice & Audio 2 x microphone

2 x speaker (Smart PA, 1W)

Connectors

Docking station

Rear POGO 8 pins (on the battery compartment)

USB type-C port

2 x dual LED (Power: R/G, Warning: R/B) Notification

GLOBAL NAVIGATION SATELLITE SYSTEM

Supported on WWAN SKU

WIRELESS

Wireless WAN (optional)

B1/2/3/4/5/7/8/12/13/17/19/20/25/26/28

/38/40/41 3G B1/2/4/5/6/8/19 Wireless I AN

IEEE 802.11 a/b/g/n/ac/ax/d/h/i/k/r/v Radio

Wi-Fi 6F WiFi Direct and Hot spot support

1x1 MU-MIMO

WPA3 personal / WPA3 enterprise / Security and encryption

Enhanced open (OWE)

Wirelss PAN

Bluetooth Bluetooth Class II. Ver. 5.x. BLE support

DATA CAPTURE

Integrated scan engine (optional)

Two scan engine options, both supporting 1D/2D symbologies Scan engines

No-scanner option available

0° or 45° Angle options

Camera

Front 8 MP

13 MP PDAF, LED flash, F/no. 2.0 (max.) Rear

NFC

NFC Forum Tag Types 1 to 5, ISO/IEC 14443A / 14443 B / 15693, Mifare Classic Reader (PCD)

1K/4K DESFire, Mifare UltraLight, Sony

FeliCa

Card emulation ISO/IEC 14443 A / 14443 B.

Mifare Classic 1K/4K (WWAN SKU only), Sony FeliCa (WWAN SKU only)

USER ENVIRONMENT

-20 °C to 50 °C or 55 °C ** Operating temperature

-4 °F to 122 °F or 131 °F **

-40 °C to 70 °C Storage temperature -40 °F to 158 °F

Humidity 95% non-condensing

Drop MII-STD-810H

1.2 m (4 ft.) to concrete and

1.55 m (5.1 ft.) to concrete with Rugged Boot, across the temperature range from -20 °C to 50 °C (-4 °F to 122 °F)

1,000 times from 0.2 m to wooden floor, Mini drops

Rain/dust proof IP65

(sealing)

Electrostatic ± 15 kV air discharge discharge ± 8 kV contact discharge

REGULATORY APPROVALS AND COMPLIANCE

RCM, CE, CB, UKCA, KC, FCC, NRCan, NBTC, WEEE, REACH, RoHS

ENTERPRISE SOLUTION



PMDM
Simple yet powerful management solution

PMDM (Point Mobile MDM) is a mobile device management solution for managing and monitoring your Point Mobile Android devices.

Centralized management of enterprise devices is vital for better productivity. You should provide a device configuration so that the workers can concentrate on their work with the device, and reduce device downtime by enabling predictive maintenance for battery replacement.



FmKinsk

Enterprise Management Tool

Makes it easy to create single-purpose devices. You can improve workforce productivity and control user's access boundaries - Restricts device usage to authorized applications only, ensuring controlled access.

PULS - ANDROID UPDATE & SECURITY

PULS is a Point Mobile's lifetime solution, which provides the Android-based Point Mobile enterprise devices with security patches for up to three years after a product launch.



Patches, Updates & Lifetime Support

Stay up-to-date with the latest security updates for up to 3 years. Conveniently update your devices in the field by FOTA.

For further information, please visit www.pointmobile.com or contact your regional sales representative

WARRANTY

Subject to the Terms and Conditions, TR54 carries 1 (one) year-warranty period from the date of purchase against the defective materials and manufacturing defects.

For further inquiries, please leave your message here: https://www.pointmobile.com/en/contactus

ACCESSORIES

Rugged Boot, Single Slot Cradle, 4-Slot Cradle, 4-Slot Battery rger, Kensington Lock, 2 x Handle (scanner SKU only)



- * Listed dimensions only apply to the no-scanner SKU configuration. ** The highest operating temperature varies by SKU.





















Corporate Headquarters

Point Mobile Co., Ltd. https://www.pointmobile.com/en/contactus +82 2 3397 7870

NA Headquarters Point Mobile Americas LLC info@pointmobileamericas.com +1 202 798 0786

Europe Headquarters Point Mobile Europe GmbH info.pmeg@pointmobile.com +49 211 1588 5913

China Headquarters Point Mobile China info@pointmobile-cn.com +86 755 8869 1169